


























Rolls



Tiles

Comfort Backing  
Make to order

		Belgium	Belgium	Belgium	
		Woven	Woven	Woven	
		95% vinyl 5% fiberglass	95% vinyl 5% fiberglass	83% vinyl 7% fiberglass 10% PET	
		Vinyl	Vinyl	Vinyl + Felt	
					
	<b>Total thickness</b>	ISO 1765	3,3 mm 0.13"	3,3 mm 0.13"	5 mm 0.20"
	<b>Total weight</b>	ISO 8543	4000 g/m <sup>2</sup> 118.0 oz/yd <sup>2</sup>	4000 g/m <sup>2</sup> 118.0 oz/yd <sup>2</sup>	3000 g/m <sup>2</sup> 88.5 oz/yd <sup>2</sup>
	<b>Roll width</b>	EN ISO 24341	ca. 200 cm ca. 6'7"	-	ca. 200 cm ca. 6'7"
	<b>Roll length</b>	EN ISO 24341	ca. 30 m 32.8 yd	-	ca. 30 m 32.8 yd
	<b>Tile size</b> 16 pcs per box	EN 994	-	50 cm x 50 cm 19.69" x 19.69"	50 cm x 50 cm 19.69" x 19.69"
	<b>Level of Use</b>	EN 1307 ASTM D5252	Class 33 Heavy commercial use	Class 33 Heavy commercial use	Class 33 Heavy commercial use
	<b>Foot traffic test</b>	ASTM D6119-12	Heavy traffic	Heavy traffic	Heavy traffic
	<b>Castor chair suitability</b>	EN 985	Continuous use	Continuous use	Continuous use
	<b>Reaction to fire</b>	EN 13501-1	Bfl-s1 Glued-stuck down	Bfl-s1 Loose laid	Bfl-s1 Loose laid
	<b>Critical radiant flux</b>	ASTM E648-10e1 NFPA	0,99 W/cm <sup>2</sup> CLASS I	0,99 W/cm <sup>2</sup> CLASS I	0,84 W/cm <sup>2</sup> CLASS I
	<b>Smoke density</b>	ASTM E622	< 300	< 300	< 300
	<b>Walking test</b>	ISO 6356 AATCC 134-2006	< 2 kv Permanently antistatic	< 2 kv Permanently antistatic	< 2 kv Permanently antistatic
	<b>Light fastness</b>	ISO 105-B02	≥ 7	≥ 7	≥ 7
	<b>Slip resistance</b>	EN 13893 ASTM C1028-07 DIN 51130 EM 13036-4	≥ 0,3 0,85 R9 65	≥ 0,3 0,85 R9 65	≥ 0,3 0,85 R9 65
	<b>Impact sound reduction</b>	ISO 10140	14 dB	14 dB	19 dB
	<b>Acoustical absorption</b>	ISO 354	$\alpha_w = 0,05$	$\alpha_w = 0,05$	$\alpha_w = 0,15$
	<b>Walking noise reduction</b>	EPLF 021029-3	SL80	SL80	SL70
	<b>Dimensional stability</b>	EN 986 ISO 2551	Meets the requirements	Meets the requirements	Meets the requirements
	<b>Thermal resistance</b>	ISO 8302	Suitable for underfloor heating	Suitable for underfloor heating	Suitable for underfloor heating
	<b>CE Certificate</b>	EN 14041	0493-CPR-0036	0493-CPR-0036	0493-CPR-0151
	<b>Environment, health and safety</b>	-	100% recyclable LEED contributing product A+ Certified REACH compliant	100% recyclable LEED contributing product A+ Certified REACH compliant	10% recycled content LEED contributing product A+ Certified REACH compliant