


























Warranty	10 years*	 Environment, health and safety
Composition	83% vinyl 7% fiberglass 10% PET	Recycled Content Yes
Backing	Vinyl + Felt	Acoustical layer 70% recycled content
 Total thickness	ISO 1765 5 mm 0.20"	Reach Compliant
 Total weight	ISO 8543 3000 g/m <sup>2</sup> 88.5 oz/yd <sup>2</sup>	LEED v4 Compliant (LEED Contributing Product)
 Roll width	EN ISO 24341 ca. 200 cm ca. 6'7"	BREEAM® International Compliant
 Roll length	EN ISO 24341 ca. 30 m 32.8 yd	CDPH Standard Method V1.2 Pass
 Tile size	EN 994 50 x 50 cm 19.69" x 19.69"	BREEAM® NOR Pass
 Level of use	EN 1307 ASTM D5252 Class 33 Heavy commercial use	French VOC Regulation A+ Certified
Foot traffic test	ASTM D6119-12 Heavy traffic	French CMR components Pass
 Castor chair suitability	EN 985 Continuous use	AGBB/ABG Pass
 Reaction to fire	EN 13501-1 Bfl-s1	Belgian VOC Regulation Pass
Critical radiant flux	ASTM E648-15e1 NFPA Class I	Indoor Air Comfort Gold Pass
Smoke density	ASTM E622 < 300	Blue Angel (RAL UZ120) Pass
 Walking test	ISO 6356 AATCC 134-2006 < 2 kv Permanently antistatic	EN 717-1 E1
 Light fastness	ISO 105-B02 ≥ 8	M1 Protocol of July 2017 Pass
 Slip resistance	EN 13893 ASTM C1028-07 DIN 51130 EM 13036-4 ≥ 0,3 0,85 R9 65	Plasticizer Content Phthalate Free
 Impact sound reduction	ISO 10140 19 dB	    
 Acoustical absorption	ISO 354 αw = 0,15	
 Walking noise reduction	EPLF 021029-3 SL70	
 Dimensional stability	EN 986 ISO 2551 Meets the requirements	
 Thermal resistance	ISO 8302 Suitable for underfloor heating	
 CE Certificate	EN 14041 0493-CPR-0151	 

CO<sub>2</sub> neutral on demand - \*Terms and conditions are available on request

0.1






















## INSTALLATION PATTERNS FOR TILES

Monolithic



Quarterturn



		 Rolls	 Tiles	 + Comfort Backing Make to order
Origin		Belgium	Belgium	Belgium
Manufacturing process		Woven	Woven	Woven
Composition		95% vinyl 5% fiberglass	95% vinyl 5% fiberglass	83% vinyl 7% fiberglass 10% PET
Backing		Vinyl	Vinyl	Vinyl + Felt
 Total thickness	ISO 1765	3,3 mm 0.13"	3,3 mm 0.13"	5 mm 0.20"
 Total weight	ISO 8543	4000 g/ m² 118.0 oz/ yd²	4000 g/ m² 118.0 oz/ yd²	3000 g/ m² 88.5 oz/ yd²
 Roll width	EN ISO 24341	ca. 200 cm ca. 6'7"	-	ca. 200 cm ca. 6'7"
 Roll length	EN ISO 24341	ca. 30 m 32.8 yd	-	ca. 30 m 32.8 yd
 Tile size 16 pcs per box	EN 994	-	50 cm x50 cm 19.69" x 19.69"	50 cm x50 cm 19.69" x 19.69"
 Level of Use	EN 1307 ASTM D5252	Class 33 Heavy commercial use	Class 33 Heavy commercial use	Class 33 Heavy commercial use
Foot traffic test	ASTM D6119-12	Heavy traffic	Heavy traffic	Heavy traffic
 Castor chair suitability	EN 985	Continuous use	Continuous use	Continuous use
 Reaction to fire	EN 13501-1	Bfls1 Glued-stuck down	Bfls1 Loose laid	Bfls1 Loose laid
Critical radiant flux	ASTM E648-10e1 NFPA	0,99 W/ cm² CLASS I	0,99 W/ cm² CLASS I	0,84 W/ cm² CLASS I
Smoke density	ASTM E622	<300	<300	<300
 Walking test	ISO 6356 AATCC 134-2006	<2 kv Permanently antistatic	<2 kv Permanently antistatic	<2 kv Permanently antistatic
 Light fastness	ISO 105-B02	≥7	≥7	≥7
 Slip resistance	EN 13893 ASTM C1028-07 DIN 51130 EN 13036-4	≥0,3 0,85 R9 65	≥0,3 0,85 R9 65	≥0,3 0,85 R9 65
 Impact sound reduction	ISO 10140	14 dB	14 dB	19 dB
 Acoustical absorption	ISO 354	$\alpha_w = 0,05$	$\alpha_w = 0,05$	$\alpha_w = 0,15$
 Walking noise reduction	EPLF 021029-3	SL80	SL80	SL70
 Dimensional stability	EN 986 ISO 2551	Meets the requirements	Meets the requirements	Meets the requirements
 Thermal resistance	ISO 8302	Suitable for underfloor heating	Suitable for underfloor heating	Suitable for underfloor heating
 CE Certificate	EN 14041	0493-CPR-0036	0493-CPR-0036	0493-CPR-0151
 Environment, health and safety	-	100% recyclable LEED contributing product A+ Certified REACH compliant	100% recyclable LEED contributing product A+ Certified REACH compliant	10% recycled content LEED contributing product A+ Certified REACH compliant